

## Silicon PIN Photodiode



21726

### FEATURES

- Package type: surface mount
- Package form: GW, RGW
- Dimensions (L x W x H in mm): 6.4 x 3.9 x 1.2
- Radiant sensitive area (in mm<sup>2</sup>): 7.5
- High radiant sensitivity
- Daylight blocking filter matched with 870 nm to 950 nm emitters
- Fast response times
- Angle of half sensitivity:  $\phi = \pm 65^\circ$
- Floor life: 168 h, MSL 3, acc. J-STD-020
- Lead (Pb)-free reflow soldering
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition


**RoHS**  
 COMPLIANT  
 HALOGEN  
**FREE**

### DESCRIPTION

VBPW34FAS and VBPW34FASR are high speed and high sensitive PIN photodiodes. It is a surface mount device (SMD) including the chip with a 7.5 mm<sup>2</sup> sensitive area and a daylight blocking filter matched with IR emitters operating at wavelength 870 nm or 950 nm.

### APPLICATIONS

- High speed detector for infrared radiation
- Infrared remote control and free air data transmissionsystems, e.g. in combination with TSFFxxxx

### PRODUCT SUMMARY

| COMPONENT  | $I_{ra}$ ( $\mu$ A) | $\phi$ (deg) | $\lambda_{0.5}$ (nm) |
|------------|---------------------|--------------|----------------------|
| VBPW34FAS  | 55                  | $\pm 65$     | 780 to 1050          |
| VBPW34FASR | 55                  | $\pm 65$     | 780 to 1050          |

#### Note

- Test conditions see table "Basic Characteristics"

### ORDERING INFORMATION

| ORDERING CODE | PACKAGING     | REMARKS                      | PACKAGE FORM     |
|---------------|---------------|------------------------------|------------------|
| VBPW34FAS     | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Gullwing         |
| VBPW34FASR    | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Reverse gullwing |

#### Note

- MOQ: minimum order quantity

### ABSOLUTE MAXIMUM RATINGS (T<sub>amb</sub> = 25 °C, unless otherwise specified)

| PARAMETER                           | TEST CONDITION                    | SYMBOL     | VALUE         | UNIT |
|-------------------------------------|-----------------------------------|------------|---------------|------|
| Reverse voltage                     |                                   | $V_R$      | 60            | V    |
| Power dissipation                   | $T_{amb} \leq 25^\circ\text{C}$   | $P_V$      | 215           | mW   |
| Junction temperature                |                                   | $T_j$      | 100           | °C   |
| Operating temperature range         |                                   | $T_{amb}$  | - 40 to + 100 | °C   |
| Storage temperature range           |                                   | $T_{stg}$  | - 40 to + 100 | °C   |
| Soldering temperature               | Acc. reflow sloder profile fig. 8 | $T_{sd}$   | 260           | °C   |
| Thermal resistance junction/ambient |                                   | $R_{thJA}$ | 350           | K/W  |



| <b>BASIC CHARACTERISTICS</b> (T <sub>amb</sub> = 25 °C, unless otherwise specified) |   |                             |      |                       |      |       |
|---|---|-----------------------------|------|-----------------------|------|-------|
| PARAMETER   | TEST CONDITION  | SYMBOL                      | MIN. | TYP.                  | MAX. | UNIT  |
| Forward voltage   | I <sub>F</sub> = 50 mA  | V <sub>F</sub>              |      | 1                     | 1.3  | V     |
| Breakdown voltage   | I <sub>R</sub> = 100 μA, E = 0  | V <sub>(BR)</sub>           | 60   |                       |      | V     |
| Reverse dark current  | V <sub>R</sub> = 10 V, E = 0  | I <sub>ro</sub>             |      | 2                     | 30   | nA    |
| Diode capacitance   | V <sub>R</sub> = 0 V, f = 1 MHz, E = 0                                      | C <sub>D</sub>              |      | 70                    |      | pF    |
|   | V <sub>R</sub> = 3 V, f = 1 MHz, E = 0                                      | C <sub>D</sub>              |      | 25                    | 40   | pF    |
| Open circuit voltage  | E <sub>e</sub> = 1 mW/cm <sup>2</sup> , λ = 950 nm                          | V <sub>o</sub>              |      | 350                   |      | mV    |
| Temperature coefficient of V <sub>o</sub>   | E <sub>e</sub> = 1 mW/cm <sup>2</sup> , λ = 950 nm                          | TK <sub>V<sub>o</sub></sub> |      | - 2.6                 |      | mV/K  |
| Short circuit current   | E <sub>e</sub> = 1 mW/cm <sup>2</sup> , λ = 950 nm                          | I <sub>k</sub>              |      | 50                    |      | μA    |
| Temperature coefficient of I <sub>k</sub>   | E <sub>e</sub> = 1 mW/cm <sup>2</sup> , λ = 950 nm                          | TK <sub>I<sub>k</sub></sub> |      | 0.1                   |      | %/K   |
| Reverse light current   | E <sub>e</sub> = 1 mW/cm <sup>2</sup> , λ = 950 nm,<br>V <sub>R</sub> = 5 V | I <sub>ra</sub>             | 45   | 55                    |      | μA    |
| Angle of half sensitivity   |   | φ                           |      | ± 65                  |      | deg   |
| Wavelength of peak sensitivity  |   | λ <sub>p</sub>              |      | 950                   |      | nm    |
| Range of spectral bandwidth   |   | λ <sub>0.5</sub>            |      | 780 to 1050           |      | nm    |
| Noise equivalent power  | V <sub>R</sub> = 10 V, λ = 950 nm   | NEP                         |      | 4 x 10 <sup>-14</sup> |      | W/√Hz |
| Rise time   | V <sub>R</sub> = 10 V, R <sub>L</sub> = 1 kΩ,<br>λ = 820 nm                 | t <sub>r</sub>              |      | 100                   |      | ns    |
| Fall time   | V <sub>R</sub> = 10 V, R <sub>L</sub> = 1 kΩ,<br>λ = 820 nm                 | t <sub>f</sub>              |      | 100                   |      | ns    |

**BASIC CHARACTERISTICS** (T<sub>amb</sub> = 25 °C, unless otherwise specified)



Fig. 1 - Reverse Dark Current vs. Ambient Temperature



Fig. 2 - Relative Reverse Light Current vs. Ambient Temperature




12787

Fig. 3 - Reverse Light Current vs. Irradiance




21743

Fig. 6 - Relative Spectral Sensitivity vs. Wavelength



12788

Fig. 4 - Reverse Light Current vs. Reverse Voltage



94 8406

Fig. 7 - Relative Radiant Sensitivity vs. Angular Displacement




948407

Fig. 5 - Diode Capacitance vs. Reverse Voltage



## PACKAGE DIMENSIONS FOR VBPW34FAS in millimeters




Drawing-No.: 6.541-5086.01-4

Issue: 1; 15.04.10

22105



## PACKAGE DIMENSIONS FOR VBPW34FASR in millimeters




Drawing-No.: 6.541-5085.01-4

Issue: 1; 15.04.10

22104



## TAPING DIMENSIONS FOR VBPW34FAS in millimeters



## TAPING DIMENSIONS FOR VBPW34FASR in millimeters






## REEL DIMENSIONS FOR VBPW34FAS AND VBPW34FASR in millimeters



21732

## SOLDER PROFILE



19841

Fig. 8 - Lead (Pb)-free Reflow Solder Profile acc. J-STD-020

## DRYPACK

Devices are packed in moisture barrier bags (MBB) to prevent the products from moisture absorption during transportation and storage. Each bag contains a desiccant.

## FLOOR LIFE

Time between soldering and removing from MBB must not exceed the time indicated in J-STD-020:

Moisture sensitivity: level 3

Floor life: 168 h

Conditions:  $T_{amb} < 30 \text{ }^\circ\text{C}$ , RH < 60 %

## DRYING

In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or recommended conditions:

192 h at 40 °C (+ 5 °C), RH < 5 %

or

96 h at 60 °C (+ 5 °C), RH < 5 %.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**